

Central Tube Steel Armor Indoor/Outdoor DTC Cable

1x24 G50 MMF ClearCurve® OM3 CT 5.0

CORNING

Corning MPC (multipurpose cable) central tube cables with corrugated steel armoring are flame-retardant, indoor/outdoor cables designed for interbuilding and intrabuilding backbones in duct, direct burial and riser applications.

The central tube cable construction, by isolating the fibers from installations and environmental rigors, provides stable and highly reliable transmission parameters. The fibers are color coded for quick, easy identification.

The cable construction, based on a central buffer tube, is compact, light, flexible and ideal for connections requiring a moderate fiber count.

These cables are designed for installation in conduits, ducts, direct burial and in-house.

Features and Benefits

Waterblocking technology

OSP (outdoor) applications

UV- and microbe-resistant

Can be installed in ducts or conduits

Corrugated steel armoring

Rodent, mechanical protection and direct buried applications

Small diameter and bend radius

Easy installation in space-constrained areas

Fibers color coding to Telcordia-Belcore

Easy identification of the individual fibers

Flame retardant

LSZH™/FRNC

Standards

Flame Test Method

Flame retardant to IEC 60332-1-2 (single cable)


Reaction to fire according to EN 50575 and EN 13501-6

Low Smoke to IEC 61034 and Zero Halogen to IEC 60754-1

Non Corrosive to IEC 60754-2



Part Number: 024TEY-13188H2G



Cross Section of Part Number: 024TEY-13188H2G

Central Tube Steel Armor Indoor/Outdoor DTC Cable

1x24 G50 MMF ClearCurve® OM3 CT 5.0

CORNING

Standards

Waterblocking IEC 60794-1-2 F5

Specifications

General Specifications	
Environment	Indoor/Outdoor
Application	Direct Buried, Duct, Vertical Riser, General Purpose Horizontal
Cable Type	Single Tube
Product Type	Corrugated Steel Armor
Flame Rating	LSZH™/FRNC
Fiber Category	50 µm MM (OM3)
Coding according to EN 60794-1-1 (DIN VDE 0888-100-1)	U-DQ(ZN)(SR)H
Previous Part Number	FWCT01-S0024-H004-DTC
Previous coding following DIN VDE 0888-3	A-DQ(ZN)(SR)H
Reaction to fire	Eca

Temperature Range	
Installation	-5 °C to 50 °C
Operation	-30 °C to 75 °C
Storage	-40 °C to 75 °C stored on drum with original packing

Cable Design	
Fiber Count	24
Fiber Coloring	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Buffer Tube Color	Yellow
Buffer Tube Diameter	3 mm
Buffer Tube Water Blocking	Thixotropic Gel
Tensile Strength Elements and/or Armoring - Layer 1	Aramid yarn with swellable elements
Number of Ripcords	2
Tensile Strength Elements and/or Armoring - Layer 2	Corrugated steel tape armor with water-swellaable tape
Outer Jacket Material	Flame-retardant, non-corrosive/low-smoke, zero-halogen (FRNC/LSZH) material
Outer Jacket Color	Black

Central Tube Steel Armor Indoor/Outdoor DTC Cable

1x24 G50 MMF ClearCurve® OM3 CT 5.0

CORNING

Cable Design

Outer Jacket Nominal Thickness	1.5 mm
Cable Marking	Meter - Handset - CE 17 EN 50575 Eca - Sine - CORNING - Fibre Optic Cable - Year - U-DQ(ZN)(SR)H 24 OM3CC CT 5.0 LSZH(TM)/FRNC

Mechanical Characteristics Cable

Nominal Outer Diameter	7.5 mm
Weight	76 kg/km
Min. Bend Radius Installation	150 mm
Min. Bend Radius Operation	110 mm
Max. Tensile Strength for Installation	1000 N
Crush Resistance	2000 N/10 cm
Fire Load	1.16 MJ/m

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Ordering Information

Part Number	024TEY-13188H2G
Product Description	Central Tube Steel Armor Indoor/Outdoor DTC Cable 1x24 G50 MMF ClearCurve® OM3 CT 5.0, Eca
EAN Code	4042673604488

Shipping Information

Maximum Delivery Length	4,000 m
-------------------------	---------



Corning Comunicacoes Opticas • Estrada do Camorim 633 • Jacarepagua CEP 22780-070 • Rio De Janeiro, RJ Brazil
+55 21 3416 5150 • FAX: +55 21 2441 2037 • www.corning.com/opcomm/csa

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2017 Corning Optical Communications. All rights reserved.